

Çift Vidalalı Extruderler Double Screw Extruders



Model	ZT 7728D	ZT 9228D	ZT 10728D
BURGU ÇAPI / Screw Diameter	77 mm	92 MM	107 mm
L/D	28D	28D	28D
ANA MOTOR GÜCÜ / Main Motor Power	51,5 kW	70 kW	109 kW
TORK / Torque	12.000 Nm	17.000 Nm	25.000 Nm
BURGU DEVRİ / Screw Speed	40 (1/min)	36 (1/mim)	36 (1/min)
ISITMA BÖLGE SAYISI / Heating Zones	7	7	7
SOĞUTMA BÖLGE SAYISI / Cooling Zones	4	4	4
YATAY DOZAJ MOTOR GÜCÜ / Horizontal Feeding Motor	1.1 kW	1.1 kW	1.1 kW
DİKEY DOZAJ MOTOR GÜCÜ / Vertical Feeding Motor	2.2 kW	2.2 Kw	2.2 kW
VAKUM POMPASI GÜCÜ / Vaccum Pomp	2.2 kW	2.2 kW	2.2 kW
KAPASİTE (Max.) / Output	400 kg/h	650 kg/h	850 kg/h
ÇALIŞMA EKSENİ / Extrusion Height	1100 mm	1100 mm	1200 mm
UZUNLUK / Length	4250 mm	4630 mm	5585 mm
GENİŞLİK / Width	1550 mm	1850 mm	1760 mm
YÜKSEKLİK / High	2250 mm	2250 mm	2320 mm
AĞIRLIK / Weight	4.000 Kg	5.500 Kg	6.500 Kg

228-10/28

